



CITY OF PLANTATION BUILDING DEPARTMENT

SHUTTER DETAIL INFORMATION BASED ON ASCE 7-22 170 MPH WIND LOAD EXPOSURE C

NOTE: HIGHLIGHT ALL MOUNTING DETAILS ON THE PRODUCT APPROVAL & INDICATE THE NUMBER OF THE OPENING THAT APPLIES NEXT TO EACH DETAIL

INFORMATION FROM PRODUCT APPROVALS

OPENING NUMBER	SHUTTER TYPE P / A / W	SHUTTER PRODUCT APP. #	SHUTTER LENGTH OR SPAN	TRIBUTARY AREA L x W	ZONE LOCATION *CORNER OR INTERIOR	FASTENER EDGE DISTANCE	OPENING DESIGN WIND LOAD PER CHART	GLASS DISTANCE SEPERATION	ANCHOR TYPE AND SPACING				BUILD OUT TRACK
									TOP	BOTTOM	SIDE	FLOOR MOUNT	
1													
2													
3													
4													
5													
6													
7													
8													
9													
10													
11													
12													
13													
14													
15													

THE INFORMATION CONTAINED HEREIN WILL BE USED TO CONDUCT INSPECTIONS.

WALL CONSTRUCTION: 1st FLOOR MASONRY WOOD 2nd FLOOR MASONRY WOOD

* Corner Zone – 10% of LEAST horizontal dimension or 40% of roof eave height, **WHICHEVER** is **SMALLER**, BUT NOT LESS THAN 4% of Least horizontal dimension or 3 ft

Shutter type: P=Panel A=Accordion W=Wroll up Tributary Area= Sq.Ft. of opening